

LTES20

IP68 Wide Window IK10 Camera Housing

Model	LTES20
Weight	1.5 kg (3.3 lb)
Certifications	CE, FCC, RoHS
Wavelength	-
Illumination Distance	-
Beam Angle	-
LEDs	-
LED Lifetime	-
Light On/Off	-
Related Products	-

*Design and specifications are subject to change without prior notice.



Features

- IP68, NEMA-6P enclosure rating
- IK10 impact resistance
- 4.5 mm thickness tempered polycarbonate with anti-fog coated
- Designed for indoor and outdoor applications
- Included sunshield

Tech Specs

Model	LTES20
Type	Indoor/Outdoor, top opening, for low operating ambient temperature
Protection Rating	<ul style="list-style-type: none"> • IP68, NEMA-6P enclosure rating • IK10
Material	Stainless and aluminum construction approve by NEMA TS2
Finish	Black polyester powder coat
Input Power	-
Output Power	-
Power Consumption	-
Dimensions (W × H × L)	204.6 mm × 90.9 mm × 175 mm (8.1 in × 3.6 in × 6.9 in)
Window Viewing Area (W × H)	140 mm × 50 mm (5.5 in × 2.0 in)
Window Thickness	4.5 mm (0.2 in), tempered polycarbonate with anti-fog coated
Internal Usable Size (W × H × L)	155 mm × 57 mm × 145 mm (6.1 in × 2.2 in × 5.7 in)
Heater Control	-
Blower Control	-
Operating Ambient Temperature	-30 °C to 70 °C (-22 °F to 158 °F)