

LTPM01

Indoor Pan and Tilt Unit for Loads up to 7 kg (15.4 lb)

IP65, maximum load of 7 kg (15.4 lb), polycarbonate and steel construction



Model	LTPM01
Power Consumption	8 W
Pan Speed	5° per second
Pan Range	0° to 355° (auto/manual)
(Movement in Horizontal Plane)	
Tilt Speed	-
Tilt Range	-50° to 50° (manual)
(Movement in Vertical Plane)	
Operating Ambient Temperature	10 °C to 35 °C (50 °F to 95 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485 (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
Protocols	Pelco D (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
Baud Rate	2,400/4,800/9,600 bps (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
Standard Setting	<ul style="list-style-type: none"> ■ Available with BNC Cable (LTPM01-A-2, LTPM01-A-3, LTPM01-A-4) ■ Available with network cable (100Mbps) (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
Dimensions (W × H × L)	179 mm × 115 mm × 180 mm (7.0 in × 4.5 in × 7.1 in)
Weight	1.8 kg (3.97 lb)

*Design and specifications are subject to change without prior notice.

Features

- Polycarbonate and steel construction
- Maximum load 7 kg (15.4 lb)
- Designed for indoor applications
- Support analogue or network cameras (optional)
- Input power: 24 V AC/110 V AC/220 V AC (available)

Available Models

Model	Support	Input Power
LTPM01-A-2	Analogue	24 V AC
LTPM01-A-3	Analogue	110 V AC
LTPM01-A-4	Analogue	220 V AC
LTPM01-N-2	Network	24 V AC
LTPM01-N-3	Network	110 V AC
LTPM01-N-4	Network	220 V AC

Tech Specs

Model	LTPM01
Maximum Load	7 kg (15.4 lb)
Type	Indoor, top load
Protection Rating	IP65, NEMA-4 enclosure rating
Material	Polycarbonate and steel construction
Finish	Beige
Input Power	<ul style="list-style-type: none"> ■ 24 V AC (LTPM01-A-2, LTPM01-N-2) ■ 110 V AC (LTPM01-A-3, LTPM01-N-3) ■ 220 V AC (LTPM01-A-4, LTPM01-N-4)