

# LTPM11

## Outdoor Pan and Tilt Unit for Loads up to 9 kg (19.8 lb)

IP66, maximum load of 9 kg (19.8 lb), speed adjustable pan and tilt, aluminum alloy construction



<b>Model</b>	<b>LTPM11</b>
<b>Temperature</b>	
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D, Pelco-P
<b>Baud Rate</b>	2,400/4,800/9,600 bps adjustable
<b>Standard Setting</b>	Available with BNC cable and network cable
<b>Dimensions (W × H × L)</b>	223 mm × 350 mm × 250 mm (8.8 in × 13.8 in × 9.8 in)
<b>Packing Dimensions (W × H × L)</b>	340 mm × 310 mm × 820 mm (13.4 in × 12.2 in × 32.3 in)
<b>Weight</b>	10 kg (22.0 lb)

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)

### Tech Specs

<b>Model</b>	<b>LTPM11</b>
<b>Maximum Load</b>	9 kg (19.8 lb)
<b>Type</b>	Indoor/Outdoor
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	High-strength aluminum
<b>Finish</b>	Beige
<b>Input Power</b>	24 V DC/24 V AC
<b>Power</b>	60 W (heater: 25 W), standby max. 15 W
<b>Consumption</b>	
<b>Pan Speed</b>	0.1° to 100° per second
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360° continuous
<b>Tilt Speed</b>	0.1° to 100° per second
<b>Tilt Range (Movement in Vertical Plane)</b>	-90° to 40°
<b>Accuracy</b>	0.1°
<b>Operating Ambient</b>	-30 °C to 60 °C (-22 °F to 140 °F)