

LTSU07

Outdoor Pan and Tilt Unit



| | |
|---|--|
| Model | LTSU07 |
| Baud Rate | 2,400/4,800/9,600/19,200 bps adjustable |
| Standard Setting | Available with BNC cable and network cable |
| Surge Protection | Built-in lightning and surge protection |
| Internal Usable Size (W × L × H) | 140 mm × 125 mm × 400 mm (5.5 in × 4.9 in × 15.7 in) (both the same) |
| Dimensions (W × L × H) | 235 mm × 740 mm × 492 mm (9.3 in × 29.1 in × 19.4 in) |
| Weight | 25.5 kg (56.2 lb) |
| Wavelength | - |
| Illumination Distance | - |
| Beam angle | - |

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Wiper (optional)
- Support analogue or network cameras (optional)

Tech Specs

| | |
|---|--|
| Model | LTSU07 |
| Type | Indoor/Outdoor |
| Protection Rating | IP66, NEMA-4X enclosure rating |
| Material | High-strength aluminum |
| Finish | Beige |
| Input Power | 24 V AC/24 V DC |
| Power Consumption | 85 W (heater: 10 W), standby max. 15 W |
| Pan Speed | 0.1° to 60° per second |
| Pan Range (Movement in Horizontal Plane) | 0° to 360° continuous |
| Tilt Speed | 0.1° to 30° per second |
| Tilt Range (Movement in Vertical Plane) | -75° to 40° |
| Accuracy | 0.0225° ± 0.003° |
| Operating Ambient Temperature | -35 °C to 65 °C (-31 °F to 149 °F) |
| Relative Humidity | 5 % to 95 % noncondensing |
| Communication Protocols | RS-485 Pelco-D, Pelco-P |