

# LTSU09

## HD Thermal Heavy PTZ System

<b>Model</b>	<b>LTSU09</b>
<b>Size (W × H × L)</b>	
<b>Dimensions (W × H × L)</b>	333 mm × 633 mm × 680 mm (13.1 in × 24.9 in × 26.8 in)
<b>Weight</b>	55 kg (121.3 lb)

\*Design and specifications are subject to change without prior notice.



### Features

- IP66, NEMA-6P enclosure rating
- Camera optional

### Tech Specs

<b>Model</b>	LTSU09
<b>Type</b>	Indoor/Outdoor
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	High-strength aluminum
<b>Finish</b>	White
<b>Input Power</b>	24 V DC/24 V AC
<b>Power</b>	100 W maximum
<b>Consumption</b>	
<b>Pan Speed</b>	0.01° to 100° per second adjustable
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360° continuous
<b>Tilt Speed</b>	0.01° to 60° per second adjustable
<b>Tilt Range (Movement in Vertical Plane)</b>	-70° to 40°
<b>Accuracy</b>	± 0.01°
<b>Operating Ambient Temperature</b>	-35 °C to 60 °C (-31 °F to 140 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D, Pelco-P
<b>Baud Rate</b>	2,400/4,800/9,600 bps adjustable
<b>Standard Setting</b>	Available with BNC cable and network cable
<b>Surge Protection</b>	Built-in lightning and surge protection
<b>Internal Usable</b>	200 mm × 180 mm × 500 mm (7.9 in × 7.1 in × 19.7 in)