

# LTSX04

## Explosion Proof Pan and Tilt Unit



<b>Model</b>	<b>LTSX04</b>
<b>Tilt Speed</b>	0.1° to 40° per second (fixed speed adjustable)
<b>Accuracy</b>	0.1°
<b>Atmospheric Pressure</b>	80 kPa to 106 kPa
<b>Operating Ambient Temperature</b>	-45 °C to 60 °C (-49 °F to 140 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D, Pelco-P
<b>Communication Speed</b>	1,200/2,400/4,800/9,600/19,200 bps adjustable
<b>Standard Setting</b>	<ul style="list-style-type: none"> <li>Available with BNC cable (<b>LTSX04-A, LTSX04-A-L</b>)</li> <li>RJ45 10/100 base (<b>LTSX04-N, LTSX04-N-L</b>)</li> </ul>
<b>Preset</b>	Up to 128
<b>Surge Protection</b>	-
<b>Internal Usable Size (Ø × L)</b>	132 mm × 260 mm (5.2 in × 10.2 in), dual housing
<b>Dimensions (W × H × L)</b>	430 mm × 430 mm × 320 mm (16.9 in × 16.9 in × 12.6 in)
<b>Weight</b>	33 kg (72.8 lb)
<b>Window Viewing Area (Ø)</b>	90 mm (3.5 in)
<b>Window Thickness</b>	10 mm (0.4 in)
<b>Number of Outlet Holes</b>	2 (internal diameter of 14 mm)
<b>Outlet Hole Thread</b>	G-3/4" × 1
<b>Size</b>	-
<b>Note</b>	-

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)
- Support thermal camera and visible camera (optional)

### Available Models

Model	Support	Material
LTSX04-A	Analogue	SS304
LTSX04-N	Network	SS304
LTSX04-A-L	Analogue	SS316L
LTSX04-N-L	Network	SS316L

### Tech Specs

Model	LTSX04
<b>Protection Rating</b>	<ul style="list-style-type: none"> <li>IP66, NEMA-4X enclosure rating</li> <li>Ex d IIC T6 Gb explosion-proof marking</li> </ul>
<b>Material</b>	<ul style="list-style-type: none"> <li>SS304 (<b>LTSX04-A, LTSX04-N</b>)</li> <li>SS316L (<b>LTSX04-A-L, LTSX04-N-L</b>)</li> </ul>
<b>Finish</b>	Stainless steel original color
<b>Input Power</b>	220 V AC, 50/60 Hz
<b>Power Consumption</b>	100 W
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360°
<b>Pan Speed</b>	0.1° to 40° per second (fixed speed adjustable)
<b>Tilt Range (Movement in Vertical Plane)</b>	-90° to 90°