

# LTAP01

## HiPoE Injector



### Features

- Up to 60 W/ 95 W (optional)
- IEEE802.3at compliant with 2-event classification
- Support 10/100/1000Base-T applications
- Surge protection according to IEC61000-4-5

### Tech Specs

|                                      |  |
|--------------------------------------|--|
| <b>Model</b>                         | LTAP01   |
| <b>PoE Output</b>                    | <ul style="list-style-type: none"> <li>• Pin assignment and polarity: 1/2 (-), 3/6 (+), 4/5 (+), 7/8 (-)</li> <li>• Output Power voltage: 54 V to 56 V DC</li> <li>• User port power: 60 W/ 95 W (<b>LTAP01-95</b>)</li> </ul> |
| <b>Connector</b>                     | Shielded RJ-45, EIA 568A and 568B  |
| <b>Data Rate</b>                     | 10/100/1000BASE-T Gigabit Ethernet   |
| <b>Input Power</b>                   | Universal 100 V to 240 V AC, 1.5 A   |
| <b>Dimensions (W × H × L)</b>        | 84 mm × 44 mm × 162 mm (3.3 in × 1.7 in × 6.4 in)  |
| <b>Weight</b>                        | 0.4 kg (0.9 lb)  |
| <b>Operating Ambient Temperature</b> | -20 °C to 50 °C (-4 °F to 113 °F)  |
| <b>Regulatory Compliance</b>         | CE (include C-Tick), LVD, FCC Class A, VCCI, RoHS  |

\*Design and specifications are subject to change without prior notice.