

# LTES08

## IP66 Stainless Steel Water Cooling Camera Housing

<b>Model</b>	<b>LTES08</b>
<b>Window Thickness</b>	8 mm (0.31 in)
<b>Window Viewing Area (Ø)</b>	70 mm (2.76 in)
<b>Weight</b>	<ul style="list-style-type: none"> <li>• 9.5 kg (20.94 lb)</li> <li>• 11.4 kg (25.13 lb) (wall mount bracket included)</li> </ul>
<b>Material</b>	AISI 304 stainless steel
<b>Cable Outlet</b>	G-3/4" × 2
<b>Heater Control</b>	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (optional)
<b>Related Products</b>	-

\*Design and specifications are subject to change without prior notice.



### Features

- IP66, NEMA-4X enclosure rating
- Water cooling camera housing
- Operating temperature range from 0 °C to 250 °C (32 °F to 482 °F)
- AISI 304 stainless steel construction
- Wall mount bracket included

### Tech Specs

<b>Model</b>	<b>LTES08</b>
<b>Type</b>	Back opening
<b>Atmospheric Pressure</b>	80 kPa to 106 kPa
<b>Operating Ambient Temperature</b>	0 °C to 250 °C (32 °F to 482 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Input Power</b>	-
<b>Inlet Water Temperature</b>	< 35 °C
<b>Water Flow Rate</b>	0.3 to 0.6 liter per second
<b>Inlet Water Pressure</b>	0.1 Mpa
<b>Dust Air Pressure</b>	0.1 Mpa to 0.4 Mpa
<b>Air Flow Rate</b>	0.3 to 0.6 liter per second
<b>Water Inlet/Outlet</b>	G-3/4" thread, 20 mm inner diameter
<b>Dimensions (W × H × L)</b>	139 mm × 183 mm × 375 mm (5.47 in × 7.20 in × 14.76 in)
<b>Internal Usable Size (W × H × L)</b>	90 mm × 80 mm × 280 mm (3.54 in × 3.15 in × 11.02 in)