

# LTES20

## IP68 Wide Window IK10 Camera Housing

<b>Model</b>	<b>LTES20</b>
<b>Weight</b>	1.5 kg (3.3 lb)
<b>Certifications</b>	CE, FCC, RoHS
<b>Wavelength</b>	-
<b>Illumination Distance</b>	-
<b>Beam Angle</b>	-
<b>LEDs</b>	-
<b>LED Lifetime</b>	-
<b>Light On/Off</b>	-
<b>Related Products</b>	-

\*Design and specifications are subject to change without prior notice.



### Features

- IP68, NEMA-6P enclosure rating
- IK10 impact resistance
- 4.5 mm thickness tempered polycarbonate with anti-fog coated
- Designed for indoor and outdoor applications
- Included sunshield

### Tech Specs

<b>Model</b>	LTES20
<b>Type</b>	Indoor/Outdoor, top opening, for low operating ambient temperature
<b>Protection Rating</b>	<ul style="list-style-type: none"> <li>• IP68, NEMA-6P enclosure rating</li> <li>• IK10</li> </ul>
<b>Material</b>	Stainless and aluminum construction approve by NEMA TS2
<b>Finish</b>	Black polyester powder coat
<b>Input Power</b>	-
<b>Output Power</b>	-
<b>Power Consumption</b>	-
<b>Dimensions (W × H × L)</b>	204.6 mm × 90.9 mm × 175 mm (8.1 in × 3.6 in × 6.9 in)
<b>Window Viewing Area (W × H)</b>	140 mm × 50 mm (5.5 in × 2.0 in)
<b>Window Thickness</b>	4.5 mm (0.2 in), tempered polycarbonate with anti-fog coated
<b>Internal Usable Size (W × H × L)</b>	155 mm × 57 mm × 145 mm (6.1 in × 2.2 in × 5.7 in)
<b>Heater Control</b>	-
<b>Blower Control</b>	-
<b>Operating Ambient Temperature</b>	-30 °C to 70 °C (-22 °F to 158 °F)