

LTEX04

IP66 Explosion Proof Camera Housing (SS304)

42 cm (16.5 in), explosion proof camera housing, included wiper and sunshield, SS304

Model	LTEX04
Window Thickness	12 mm (0.47 in)
Window Viewing Area (Ø)	69.5 mm (2.74 in)
Weight	<ul style="list-style-type: none"> • 11 kg (24.25 lb) • 12.8 kg (28.22 lb) (wall mount bracket included)
Material	<ul style="list-style-type: none"> • AISI 304 stainless steel (LTEX04) • AISI 316L stainless steel (LTEX04-L)
Heater Control	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (optional)
Related Products	LTMH08, LTPX01, LTMH08-L

*Design and specifications are subject to change without prior notice.



Features

- IP66, NEMA-4X enclosure rating
- Operating temperature range from -25 °C to 60 °C (-13 °F to 140 °F)
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)
- Included wiper and sunshield

Available Models

Model	Material
LTEX04	AISI 304 stainless steel
LTEX04-L	AISI 316L stainless steel

Tech Specs

Model	LTEX04
Type	Back opening
Atmospheric Pressure	80 kPa to 106 kPa
Operating Ambient Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	<ul style="list-style-type: none"> • Ex d IIC T6 Gb explosion-proof marking • IP66, NEMA-4X enclosure rating
Input Power	85 V AC to 265 V AC, 24 V AC
Dimensions (W × H × L)	195 mm × 194 mm × 420 mm (7.68 in × 7.64 in × 16.54 in)
Internal Usable Size (Ø × L)	80 mm × 210 mm (3.15 in × 8.27 in)