

# LTMH15

## Length Adjustable Cable Managed Bracket

Adjustable length from 465 mm to 2074 mm (18.3 in to 81.7 in) (optional)



### Features

- Designed for box camera, dome camera, camera housing mounting applications
- Aluminum construction
- Easy length adjustable
- Adjustable length up to 465 mm to 2074 mm (18.3 in to 81.7 in) (optional)
- Plate and screw head (available)

### Available Models

Model	Adjustable Length	Head
LTMH15-P	305 mm to 465 mm (12.0 in to 18.3 in)	Plate
LTMH15-S	305 mm to 465 mm (12.0 in to 18.3 in)	Screw
LTMH15L-P	617 mm to 1004 mm (24.3 in to 39.5 in)	Plate
LTMH15L-S	617 mm to 1004 mm (24.3 in to 39.5 in)	Screw
LTMH15XL-P	1140 mm to 2074 mm (44.9 in to 81.7 in)	Plate
LTMH15XL-S	1140 mm to 2074 mm (44.9 in to 81.7 in)	Screw

### Tech Specs

Model	LTMH15
Maximum Load	2 kg (4.4 lb)
Material	Aluminum
Finish	Sliver polyester powder coat
Dimensions (L × Ø)	<ul style="list-style-type: none"> <li>• 305 mm to 465 mm × 120 mm (12.0 in to 18.3 in × 4.7 in) (LTMH15-P, LTMH15-S)</li> <li>• 617 mm to 1004 mm × 120 mm (24.3 in to 39.5 in × 4.7 in) (LTMH15L-P, LTMH15L-S)</li> </ul>

Model	LTMH15
Weight	<ul style="list-style-type: none"> <li>• 1140 mm to 2074 mm (44.9 in to 81.7 in) (LTMH15XL-P, LTMH15XL-S)</li> <li>• 460 g (1.0 lb) (LTMH15-P, LTMH15-S)</li> <li>• 633 g (1.4 lb) (LTMH15L-P, LTMH15L-S)</li> <li>• 1 kg (2.2 lb) (LTMH15XL-P, LTMH15XL-S)</li> </ul>
Related Products	-

\*Design and specifications are subject to change without prior notice.