

LTPD02

Outdoor PTZ Dome Housing

20.8 cm (8.2 in), PTZ speed dome housing



Model	LTPD02
Speed	
Standard Setting	Available with BNC cable
OSD menu	Available
Preset	Up to 160 preset positions, 1 scanning modes, 4 tracks (path record), 8 patro groups (each patrol group patrol point 2 to 64)
Surge Protection	-
Dimensions (W × H × L)	208 mm × 433 mm × 278 mm (8.2 in × 17.0 in × 10.9 in)
Internal Usable Size (W × H × L)	55 mm × 60 mm × 120 mm (2.2 in × 2.4 in × 4.7 in)
Weight	3 kg (6.6 lb)
Wavelength	850 nm
Illumination Distance	2 m to 120 m (6.6 ft to 393.7 ft), 1 way short distance, 2 way long distance LED
Beam Angle	-
LEDs	9 pieces
LED Lifetime	> 25,000 hours
Light On/Off	On when illumination is lower than 4 lux
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Die-cast aluminum construction

Tech Specs

Model	LTPD02
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Die-cast aluminum, ABS
Finish	White
Input Power	12 V DC
Power	30 W maximum
Consumption	
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Pan Speed	0.5 to 160° per second
Tilt Range (Movement in Vertical Plane)	0° to 90°
Tilt Speed	0.5 to 30° per second
Accuracy	0.1°
Atmospheric Pressure	-
Operating Ambient Temperature	-10 °C to 50 °C (-14 °F to 122 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485, LAN
Protocols	Pelco-D (9600 bps)
Communication	2,400 bps, 4,800 bps, 9,600 bps adjustable