

# LTPM01

Indoor Pan and Tilt Unit for Loads up to 7 kg (15.4 lb)

IP65, maximum load of 7 kg (15.4 lb), polycarbonate and steel construction



<b>Model</b>	<b>LTPM01</b>
<b>Power Consumption</b>	8 W
<b>Pan Speed</b>	5° per second
<b>Pan Range</b>	0° to 355° (auto/manual)
<b>(Movement in Horizontal Plane)</b>	
<b>Tilt Speed</b>	-
<b>Tilt Range</b>	-50° to 50° (manual)
<b>(Movement in Vertical Plane)</b>	
<b>Operating Ambient Temperature</b>	10 °C to 35 °C (50 °F to 95 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485 (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
<b>Protocols</b>	Pelco D (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
<b>Baud Rate</b>	2,400/4,800/9,600 bps (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
<b>Standard Setting</b>	<ul style="list-style-type: none"> <li>■ Available with BNC Cable (LTPM01-A-2, LTPM01-A-3, LTPM01-A-4)</li> <li>■ Available with network cable (100Mbps) (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)</li> </ul>
<b>Dimensions (W × H × L)</b>	179 mm × 115 mm × 180 mm (7.0 in × 4.5 in × 7.1 in)
<b>Weight</b>	1.8 kg (3.97 lb)

\*Design and specifications are subject to change without prior notice.

## Features

- Polycarbonate and steel construction
- Maximum load 7 kg (15.4 lb)
- Designed for indoor applications
- Support analogue or network cameras (optional)
- Input power: 24 V AC/110 V AC/220 V AC (available)

## Available Models

Model	Support	Input Power
LTPM01-A-2	Analogue	24 V AC
LTPM01-A-3	Analogue	110 V AC
LTPM01-A-4	Analogue	220 V AC
LTPM01-N-2	Network	24 V AC
LTPM01-N-3	Network	110 V AC
LTPM01-N-4	Network	220 V AC

## Tech Specs

<b>Model</b>	LTPM01
<b>Maximum Load</b>	7 kg (15.4 lb)
<b>Type</b>	Indoor, top load
<b>Protection Rating</b>	IP65, NEMA-4 enclosure rating
<b>Material</b>	Polycarbonate and steel construction
<b>Finish</b>	Beige
<b>Input Power</b>	<ul style="list-style-type: none"> <li>■ 24 V AC (LTPM01-A-2, LTPM01-N-2)</li> <li>■ 110 V AC (LTPM01-A-3, LTPM01-N-3)</li> <li>■ 220 V AC (LTPM01-A-4, LTPM01-N-4)</li> </ul>