

# LTPM03

## Outdoor Pan and Tilt Unit for Loads up to 6 kg (13.2 lb)

IP66, maximum load of 6 kg (13.2 lb), speed adjustable pan and tilt, aluminum alloy construction



<b>Model</b>	<b>LTPM03</b>
<b>Tilt Speed</b>	0.2° to 7.5° per second
<b>Pan Range (Movement in Horizontal Plane)</b>	<ul style="list-style-type: none"> <li>• 0° to 360° continuous (LTPM03)</li> <li>• Limit pan range (selectable) (LTPM03-L)</li> </ul>
<b>Tilt Range (Movement in Vertical Plane)</b>	-60° to 30°
<b>Accuracy</b>	±0.1°
<b>Operating Ambient Temperature</b>	-10 °C to 50 °C (-14 °F to 122 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D, Pelco-P
<b>Baud Rate</b>	2,400/4,800/9,600 bps adjustable
<b>Standard Setting</b>	Available with BNC or network cable (selectable)
<b>OSD menu</b>	Available
<b>Preset</b>	Up to 130
<b>Surge Protection</b>	GB/T17626.5-2008
<b>Dimensions (W × H × L)</b>	165 mm × 263 mm × 146 mm (6.5 in × 10.4 in × 5.8 in)
<b>Weight</b>	6.5 kg (14.3 lb)
<b>Note</b>	-

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- Maximum load 6 kg (13.2 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Input power: 24 V DC
- Support analogue or network cameras (optional)

### Available Models

Model	Pan Range
<b>LTPM03</b>	0° to 360° continuous
<b>LTPM03-L</b>	Limit pan range (selectable)

### Tech Specs

Model	LTPM03
<b>Maximum Load</b>	6 kg (13.2 lb)
<b>Type</b>	Indoor/Outdoor, top load
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	Aluminum alloy
<b>Finish</b>	Beige
<b>Input Power</b>	24 V DC
<b>Power</b>	30 W
<b>Consumption</b>	
<b>Pan Speed</b>	0.2° to 15° per second