

LTPM05

Outdoor Pan and Tilt Unit for Loads up to 15 kg (33.1 lb)

IP66, maximum load of 15 kg (33.1 lb), speed adjustable pan and tilt, aluminum alloy construction



| | |
|---------------------------------------|--|
| Model | LTPM05 |
| Tilt Speed | 0.01° to 30° per second |
| Pan Range | 0° to 360° continuous |
| (Movement in Horizontal Plane) | |
| Tilt Range | -75° to 40° (-90° to 40° optional) |
| (Movement in Vertical Plane) | |
| Accuracy | 0.225° ± 0.003° |
| Operating Ambient Temperature | -35 °C to 65 °C (-31 °F to 149 °F) |
| Relative Humidity | 5 % to 95 % noncondensing |
| Auto Scan | Up to 5 lines, based on OSD function, configurable speed |
| Auto Cruise | Up to 8 groups, based on OSD function, configurable speed |
| Continuous Scan | 8 line, configurable speed and angles |
| Angles Display | Support |
| Communication | RS-485 |
| Protocols | Pelco-D, Pelco-P |
| Baud Rate | 2,400/4,800/9,600/19,200 bps adjustable |
| Standard Setting | <ul style="list-style-type: none"> Available with BNC Cable (LTPM05-A) Available with network cable (100Mbps) (LTPM05-N) |
| OSD menu | Available |
| Preset | Up to 80 |
| Lens Driven | 10 V/6 V software control and adaptive |
| Lens Interface | Support (pan and tilt preset configuration interface) |
| Surge Protection | GB/T17626.5-2008 |
| Dimensions (W × H × L) | 249 mm × 230 mm × 302 mm (9.80 in × 9.06 in × 11.89 in) |
| Weight | 15 kg (33.1 lb) |
| Note | - |

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- Maximum load 15 kg (33.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Input power: 24 V AC
- Support analogue or network cameras (optional)

Available Models

| Model | Support |
|-----------------|----------|
| LTPM05-A | Analogue |
| LTPM05-N | Network |

Tech Specs

| Model | LTPM05 |
|--------------------------|---|
| Maximum Load | 15 kg (33.1 lb) |
| Type | Indoor/Outdoor, top load |
| Protection Rating | IP66, NEMA-4X enclosure rating |
| Material | Aluminum alloy |
| Finish | Beige |
| Input Power | 24 V AC ± 25 % |
| Power Consumption | max. 85 W (heater off), max. 95 W (heater on) |
| Pan Speed | 0.01° to 60° per second |