

LTPM14

Outdoor Pan and Tilt Unit for Loads up to 20 kg (44.1 lb)

IP66, maximum load of 20 kg (44.1 lb), speed adjustable pan and tilt, aluminum alloy construction



Model	LTPM14
Power protection	TVS 8000V lightn --proof, surge proof, in line with GB/T17626.5 Level
Accuracy	± 0.01°
Pan Speed	0.01° to 100° per second
Pan Range	0° to 360° continuous
(Movement in Horizontal Plane)	
Tilt Speed	0.01° to 70° per second
Tilt Range	-55° to 60°
(Movement in Vertical Plane)	
Power	60 W maximum
Consumption	
Operating Ambient Temperature	-40 °C to 65 °C (-40 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485/RS-422
Protocols	Pelco-D
Baud Rate	9,600 bps adjustable
Standard Setting	<ul style="list-style-type: none"> • Available with BNC Cable (LTPM14-A-6, LTPM14-A-7) • Available with network cable (100Mbps) (LTPM14-N-6, LTPM14-N-7)
OSD menu	Available
Preset	128
Dimensions (W × H × L)	198 mm × 345 mm × 335 mm (7.8 in × 13.6 in × 13.2 in)
Weight	18 kg (39.7 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Maximum load 20 kg (44.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)
- Input power: 24 V DC/ 48 V DC (optional)

Available Models

Model	Support	Input Power
LTPM14-A-6	Analogue	24 V DC
LTPM14-A-7	Analogue	48 V DC
LTPM14-N-6	Network	24 V DC
LTPM14-N-7	Network	48 V DC

Tech Specs

Model	LTPM14
Maximum Load	20 kg (44.1 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	<ul style="list-style-type: none"> • 24 V DC (LTPM14-A-6, LTPM14-N-6) • 48 V DC (LTPM14-A-7, LTPM14-N-7)