

LTSU07

Outdoor Pan and Tilt Unit



Model	LTSU07
Baud Rate	2,400/4,800/9,600/19,200 bps adjustable
Standard Setting	Available with BNC cable and network cable
Surge Protection	Built-in lightning and surge protection
Internal Usable Size (W × L × H)	140 mm × 125 mm × 400 mm (5.5 in × 4.9 in × 15.7 in) (both the same)
Dimensions (W × L × H)	235 mm × 740 mm × 492 mm (9.3 in × 29.1 in × 19.4 in)
Weight	25.5 kg (56.2 lb)
Wavelength	-
Illumination Distance	-
Beam angle	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Wiper (optional)
- Support analogue or network cameras (optional)

Tech Specs

Model	LTSU07
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	High-strength aluminum
Finish	Beige
Input Power	24 V AC/24 V DC
Power Consumption	85 W (heater: 10 W), standby max. 15 W
Pan Speed	0.1° to 60° per second
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Tilt Speed	0.1° to 30° per second
Tilt Range (Movement in Vertical Plane)	-75° to 40°
Accuracy	0.0225° ± 0.003°
Operating Ambient Temperature	-35 °C to 65 °C (-31 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication Protocols	RS-485 Pelco-D, Pelco-P