

# LTCN08

## Cámara domo 8 MP



### Features

- IP66, NEMA-4X enclosure rating
- 1/2.5-inch Sony Starvis 8.51 MP image sensor
- 0.05 lux minimum illumination in color mode
- Megapixel f = 3.6 to 11 mm varifocal lens
- H.265/H.264/MJPEG compression
- Power over Ethernet (PoE), IEEE 802.3af
- Operating temperature range from -10 °C to 50 °C (14 °F to 122 °F)
- Automatic removable IR cut filter for IR sensitivity at night
- ONVIF compliant

### Tech Specs

<b>Model</b>	LTCN08
<b>Type</b>	Dome camera
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Image Sensor</b>	1/2.5-inch Sony Starvis 8.51 MP image sensor
<b>Lens</b>	Megapixel f = 3.6 to 11 mm varifocal lens
<b>Effective Pixels</b>	3864 × 2202
<b>Minimum Illumination</b>	<ul style="list-style-type: none"> <li>■ Color mode: 0.05 lux at F 1.2, AGC on</li> <li>■ Black and white mode: 0 lux (LED on)</li> </ul>
<b>Electronic Shutter Range</b>	1/30 s to 1/30,000 s
<b>IR Cut Filter</b>	Automatically switches
<b>Wide Dynamic Range (WDR)</b>	Digital WDR
<b>Digital Noise Reduction (DNR)</b>	2D/3DNR
<b>Video Compression</b>	H.265/H264/MJPEG
<b>Motion Detection</b>	432 zone (of/off, 1 to 5 step)
<b>Privacy Masking</b>	Off/On (16 programmable zones)
<b>Day and Night</b>	Color/B/W/Auto
<b>Frame Rate</b>	Max. 30 fps for all resolution
<b>Streaming Capability</b>	Triple stream (stream 1, 2, 3) RTP/RTSP, Unicast RTP, Multicast RTP
<b>Certifications</b>	ONVIF, PSIA, CGI, ISAPI, GB28181
<b>Supported Protocols</b>	TCP/IP, UDP/IP, RTP, RTSP, RTCP, NTP, HTTP, DHCP, FTP, SMTP, DNS, DDNS
<b>ONVIF</b>	Ver 17.06
<b>LEDs</b>	24 pieces
<b>Illumination Distance</b>	20 m (65.6 ft)
<b>Operating Ambient Temperature</b>	-10 °C to 50 °C (14 °F to 122 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Input Power</b>	12 V DC ± 10 %/PoE current Max. 750 mA
<b>Power Consumption</b>	Max. 12 W
<b>Dimensions (Ø × H)</b>	136 mm × 115 mm (5.4 in × 4.5 in)
<b>Weight</b>	600 g (1.3 lb)

\*Design and specifications are subject to change without prior notice.