

LTCN12

Módulo de cámara con zoom (2 MP, 60 fps, 86X)



Features

- 1/2-inch Sony Exmor CMOS
- 0.0001 lux minimum illumination in black and white mode
- H.265/H.264/H.264H/MJPEG compression
- 60 frame per second at 1920 × 1080
- 2-way audio
- Operating temperature range from -30 °C to 60 °C (-22 °F to 140 °F)
- ONVIF compliant

Tech Specs

| | |
|--------------------------------------|--|
| Model | LTCN12 |
| Type | Network camera module |
| Image Sensor | 1/2-inch Sony Exmor CMOS |
| Lens | f = 10 mm to 860 mm (86X), F/2.0 to F/6.8, auto focus, auto iris |
| Digital Zoom | 4X |
| View of Angle | 42° (wide) to 0.44° (tele) |
| Effective Pixels | 1920 × 1080 |
| Minimum Illumination | <ul style="list-style-type: none"> ■ Color: 0.001 lux at (F/2.0, AGC on) ■ Day and Night: 0.0001 lux at (F/2.0 AGC on) |
| Electronic Shutter Range | 1/3 to 1/30,000 second |
| Wide Dynamic Range (WDR) | 3D |
| Digital Noise Reduction (DNR) | 0 to 5, total 6 steps |
| Video Compression | H.265/H.264/H.264H/MJPEG |
| Audio Compression | G.711/AAC |
| Frame Rate | 60 frames per second (1080p) |
| WhiteBalance | Auto/indoor/outdoor/OPW/ATW/manual |
| Auto gain | Auto/Manual |
| PTZ Control Protocol | 40 types of control protocol including Pelco D/Pelco P |
| Certifications | ONVIF, PSIA |
| Operating Ambient Temperature | -30 °C to 60 °C (-22 °F to 140 °F) |
| Relative Humidity | 5 % to 95 % noncondensing |
| Input Power | 12 V DC |
| Power Consumption | 8.4 W maximum |
| Dimensions (W × H × L) | 145 mm × 150 mm × 395 mm (5.7 in × 5.9 in × 15.6 in) |
| Weight | 5.6 kg (12.3 lb) |

*Design and specifications are subject to change without prior notice.