

# LTCN14

Módulo de cámara con zoom (8 MP, 60 fps, 40X)



## Features

- 1/1.8-inch Sony Exmor CMOS
- 0.005 lux minimum illumination in black and white mode
- H.265/H.264/H.264H/MJPEG compression
- 60 frame per second at 3840 × 2160
- 2-way audio
- Operating temperature range from -10 °C to 50 °C (14 °F to 122 °F)
- ONVIF compliant

## Tech Specs

<b>Model</b>	LTCN14
<b>Type</b>	Network camera module
<b>Image Sensor</b>	1/1.8-inch Sony Exmor CMOS
<b>Lens</b>	f = 6.5 mm to 260 mm (40X), f/1.4 to f/4.9, auto focus, auto iris
<b>Digital Zoom</b>	16X
<b>View of Angle</b>	64.1° (wide) to 2.0° (tele)
<b>Effective Pixels</b>	3840 × 2160
<b>Minimum Illumination</b>	<ul style="list-style-type: none"> <li>▪ Color: 0.14 lux at (F/1.4, AGC on)</li> <li>▪ Day and Night: 0.005 lux at (F/1.4 AGC on)</li> </ul>
<b>Electronic Shutter Range</b>	1/3 to 1/100,000 second
<b>Wide Dynamic Range (WDR)</b>	3D
<b>Digital Noise Reduction (DNR)</b>	0 to 5, total 6 steps
<b>Video Compression</b>	H.265/H.264/H.264H/MJPEG
<b>Audio Compression</b>	G.711/AAC
<b>Frame Rate</b>	60 frames per second at 3840 × 2160
<b>WhiteBalance</b>	Auto/indoor/outdoor/OPW/ATW/manual
<b>Auto gain</b>	Auto/Manual
<b>PTZ Control</b>	-
<b>Protocol</b>	
<b>Certifications</b>	ONVIF, PSIA
<b>Operating Ambient Temperature</b>	-10 °C to 50 °C (14 °F to 122 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Input Power</b>	12 V DC
<b>Power Consumption</b>	13.6 W maximum
<b>Dimensions (W × H × L)</b>	73 mm × 78 mm × 156 mm (2.9 in × 3.1 in × 6.1 in)
<b>Weight</b>	682 g (1.5 lb)

\*Design and specifications are subject to change without prior notice.