

LTEG07

Carcasa para cámara con doble ventana y cierre de apertura superior IP66

Construcción de aluminio con tapas de plástico en los extremos, soporte interno para gestionar el cable, tamaño interno utilizable (ancho × alto × largo): 108 mm × 130 mm × 350 mm (un solo lado)



Model	Wiper	Heater	Blower	Input Power
LTEG07-W-0-4	+			220 V AC
LTEG07-W-1-2	+	+		24 V AC
LTEG07-W-1-4	+	+		220 V AC
LTEG07-W-2-2	+		+	24 V AC
LTEG07-W-2-4	+		+	220 V AC
LTEG07-W-3-2	+	+	+	24 V AC
LTEG07-W-3-4	+	+	+	220 V AC

Tech Specs

Features

- IP66, NEMA-4X enclosure rating
- Designed for indoor and outdoor applications
- Input power: 24 V AC/220 V AC (available)
- Built-in heater, blower, wiper and sunshield (optional)
- Adjustable sliding camera tray
- Cable entry glands and mounting holes on bottom of housing
- Hinged top opening for easy installation and camera setup
- Side-mount link-lock latches for security
- Two different size optional

Available Models

Model	Dimention
LTEG07	Normal size
LTEG07L	Large size

*The different sizes in above table have the following models available.

Model	Wiper	Heater	Blower	Input Power
LTEG07-0				
LTEG07-1-2		+		24 V AC
LTEG07-1-4		+		220 V AC
LTEG07-2-2			+	24 V AC
LTEG07-2-4			+	220 V AC
LTEG07-3-2		+	+	24 V AC
LTEG07-3-4		+	+	220 V AC
LTEG07-W-0-2	+			24 V AC

Model	LTEG07
Type	Indoor/Outdoor, top opening, link-lock latches
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Extruded aluminum body and sunshield
Finish	White polyester powder coat
Input Power	<ul style="list-style-type: none"> • 24 V AC (LTEG07-1-2, LTEG07-2-2, LTEG07-3-2, LTEG07-W-0-2, LTEG07-W-1-2, LTEG07-W-2-2, LTEG07-W-3-2) • 220 V AC (LTEG07-1-4, LTEG07-2-4, LTEG07-3-4, LTEG07-W-0-4, LTEG07-W-1-4, LTEG07-W-2-4, LTEG07-W-3-4)
Power Consumption	<ul style="list-style-type: none"> • Heater: 10 W • Blower: 2 W • Wiper: 5 W
Network Interface	-
Dimensions (W × H × L)¹	<ul style="list-style-type: none"> • LTEG07-0, LTEG07-W-1: 366 mm × 185 mm × 524 mm (14.4 in × 7.3 in × 20.6 in) • LTEG07L-0, LTEG07L-W-1: 366 mm × 185 mm × 600 mm (14.4 in × 7.3 in × 23.6 in)
Window Viewing Area (W × H)	100 mm × 90 mm (3.9 in × .55 in)
Window Thickness	2 mm (0.08 in), tempered glass
Internal Usable Size (W × H × L)¹	<ul style="list-style-type: none"> • LTEG07-0, LTEG07-W-1: 108 mm × 130 mm × 350 mm (4.3 in × 5.1 in × 13.8 in), single side • LTEG07L-0, LTEG07L-W-1: 108 mm × 130 mm × 426 mm (4.3 in × 5.1 in × 16.8 in), single side
Heater Control	On at 8 °C ± 5 °C (46 °F ± 18 °F), off at 20 °C ± 3 °C (68 °F ± 11 °F) (LTEG07-1-2, LTEG07-1-4, LTEG07-3-2, LTEG07-3-4, LTEG07-W-1-2, LTEG07-W-1-4, LTEG07-W-3-2, LTEG07-W-3-4)
Blower Control	On at 38 °C ± 5 °C (100 °F ± 18 °F), off at 20 °C ± 3 °C (68 °F ± 11 °F) (LTEG07-2-2, LTEG07-2-4, LTEG07-3-2, LTEG07-3-4, LTEG07-W-2-2, LTEG07-W-2-4, LTEG07-W-3-2, LTEG07-W-3-4)
Operating Ambient Temperature	-35 to 65 °C (-95 °F to 149 °F)
Weight¹	<ul style="list-style-type: none"> • LTEG07-0: 6.8 kg (15.0 lb) • LTEG07L-0: 7.8 kg (17.2 lb) • Wiper: 0.3 kg (0.7 lb)
Certifications	CE, FCC, RoHS
Related Products	-

1. The specs for LTEG07-_- and LTEG07L-_- are the same as LTEG07-0 and LTEG07L-0 respectively.

*Design and specifications are subject to change without prior notice.