

LTEX04

Carcasa de cámara a prueba de explosión IP66 (SS304)

13 cm (5 in), carcasa de domo a prueba de explosiones, SS304

Model	LTEX04
Size (Ø × L)	
Window Thickness	12 mm (0.47 in)
Window Viewing Area (Ø)	69.5 mm (2.74 in)
Weight	<ul style="list-style-type: none"> • 11 kg (24.25 lb) • 12.8 kg (28.22 lb) (wall mount bracket included)
Material	<ul style="list-style-type: none"> • AISI 304 stainless steel (LTEX04) • AISI 316L stainless steel (LTEX04-L)
Heater Control	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (optional)
Related Products	LTMH08, LTPX01, LTMH08-L

*Design and specifications are subject to change without prior notice.



Features

- IP66, NEMA-4X enclosure rating
- Operating temperature range from -25 °C to 60 °C (-13 °F to 140 °F)
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)
- Included wiper and sunshield

Available Models

Model	Material
LTEX04	AISI 304 stainless steel
LTEX04-L	AISI 316L stainless steel

Tech Specs

Model	LTEX04
Type	Back opening
Atmospheric Pressure	80 kPa to 106 kPa
Operating Ambient Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	<ul style="list-style-type: none"> • Ex d IIC T6 Gb explosion-proof marking • IP66, NEMA-4X enclosure rating
Input Power	85 V AC to 265 V AC, 24 V AC
Dimensions (W × H × L)	195 mm × 194 mm × 420 mm (7.68 in × 7.64 in × 16.54 in)
Internal Usable	80 mm × 210 mm (3.15 in × 8.27 in)