

# LTILO3

## Iluminador láser infrarrojo

Distancia de iluminación de hasta 1.000 m (3.280 pies)



<b>Model</b>	<b>LTILO3</b>
<b>Beam Angle</b>	1.5° to 68°, motor driven
<b>Illumination</b>	up to 1,000 m (3,280 ft)
<b>Distance</b>	
<b>Laser Lifetime</b>	30,000 hours
<b>Communication</b>	RS485

\*Design and specifications are subject to change without prior notice.

### Features

- Illuminator with distance up to 1,000 m (3,280 ft)
- Motor driven beam angle from 1° to 30° adjustable
- Synchronized with camera zoom
- Input power: 12 V DC
- Semi-covert (808 nm), covert 940 nm, and 980 nm infrared Laser optional

### Available Models

Model	Wavelength
<b>LTILO3</b>	808 nm
<b>LTILO3-940</b>	940 nm
<b>LTILO3-980</b>	980 nm

### Tech Specs

Model	LTILO3
<b>Input Power</b>	12 V DC
<b>Power</b>	25 W
<b>Consumption</b>	
<b>Dimensions (W × H × L)</b>	66 mm × 69 mm × 132 mm (2.6 in × 2.7 in × 5.2 in)
<b>Operating Ambient Temperature</b>	-20 °C to 50 °C (-4 °F to 122 °F)
<b>Storage Temperature</b>	-40 °C to 80 °C (-40 °F to 176 °F)
<b>Weight</b>	470 g (1.0 lb)
<b>Wavelength</b>	<ul style="list-style-type: none"> <li>• 808 ± 5 nm (<b>LTILO3</b>)</li> <li>• 940 nm (<b>LTILO3-940</b>)</li> <li>• 980 nm (<b>LTILO3-980</b>)</li> </ul>