

LTPM03

Unidad de Pan Tilt para exteriores

IP66, carga máxima de 9 kg (19,8 lb), velocidad de giro e inclinación ajustable, construcción de aleación de aluminio



| | |
|---------------------------------------|--|
| Model | LTPM03 |
| (Movement in Horizontal Plane) | |
| Tilt Range | -60° to 10° |
| (Movement in Vertical Plane) | |
| Accuracy | 0.4° |
| Operating Ambient Temperature | -10 °C to 50 °C (-14 °F to 122 °F) |
| Relative Humidity | 5 % to 95 % noncondensing |
| Communication | RS-485 |
| Protocols | Pelco-D, Pelco-P |
| Baud Rate | 2,400/4,800/9,600/19,200 bps adjustable |
| Standard Setting | <ul style="list-style-type: none"> Available with BNC Cable (LTPM03-A-6) Available with network cable (100Mbps) (LTPM03-N-6) |
| OSD menu | Available |
| Preset | Up to 226 |
| Surge Protection | GB/T17626.5-2008 |
| Dimensions (W × H × L) | 165 mm × 263 mm × 146 mm (6.5 in × 10.4 in × 5.8 in) |
| Weight | 7 kg (15.4 lb) |
| Note | - |

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- Maximum load 9 kg (19.8 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Input power: 24 V DC
- Support analogue or network cameras (optional)

Available Models

| Model | Support |
|-------------------|----------|
| LTPM03-A-6 | Analogue |
| LTPM03-N-6 | Network |

Tech Specs

| Model | LTPM03 |
|--------------------------|--------------------------------|
| Maximum Load | 9 kg (19.8 lb) |
| Type | Indoor/Outdoor, top load |
| Protection Rating | IP66, NEMA-4X enclosure rating |
| Material | Aluminum alloy |
| Finish | Beige |
| Input Power | 24 V DC |
| Power | 30 W |
| Consumption | |
| Pan Speed | 0.4° to 10° per second |
| Tilt Speed | 0.4° to 2.5° per second |
| Pan Range | 0° to 360° continuous |