

LTPM04

Unidad de Pan Tilt para exteriores para cargas de hasta 15 kg (33,1 lb)

IP66, carga máxima de 15 kg (33,1 lb), velocidad de pan tilt ajustable, construcción de aleación de aluminio



Model	LTPM04
Consumption	
Pan Speed	0.4° to 10° per second
Pan Range	0° to 360° continuous
(Movement in Horizontal Plane)	
Tilt Speed	0.4° to 2.5° per second
Tilt Range	• -60° to 10° for load 20 kg (44.1 lb) (factory setting)
(Movement in Vertical Plane)	
Accuracy	0.4°
Operating Ambient Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	• Available with BNC Cable (LTPM04-A-6, LTPM04S-A-6) • Available with network cable (100Mbps) (LTPM04-N-6, LTPM04S-N-6)
OSD menu	Available
Heater	Optional
Dimensions (W × H × L)	• 301 mm × 217 mm × 184 mm (11.9 in × 8.5 in × 7.2 in) (LTPM04-A-6, LTPM04S-A-6) • 610 mm × 217 mm × 184 mm (24.0 in × 8.5 in × 7.2 in) (LTPM04-N-6, LTPM04S-N-6)
Weight	9.3 kg (20.5 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Maximum load 15 kg (33.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)

Available Models

Model	Load	Support	Input Power
LTPM04-A-6	Top load	Analogue	24 V DC
LTPM04-N-6	Top load	Network	24 V DC
LTPM04S-A-6	Side load	Analogue	24 V DC
LTPM04S-N-6	Side load	Network	24 V DC

Tech Specs

Model	LTPM04
Maximum Load	15 kg (33.1 lb)
Type	Indoor/Outdoor, top load (LTPM04-A-6, LTPM04-N-6), side load (LTPM04S-A-6, LTPM04S-N-6)
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	24 V DC
Power	40 W