

LTPM05

Unidad de Pan Tilt para exteriores

IP66, carga máxima de 15 kg (33,1 lb), velocidad de giro e inclinación ajustable, construcción de aleación de aluminio



Model	LTPM05
(Movement in Horizontal Plane)	
Tilt Range	-75° to 40° (-90° to 40° optional)
(Movement in Vertical Plane)	
Accuracy	0.225° ± 0.003°
Operating Ambient Temperature	-35 °C to 65 °C (-31 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Auto Scan	Up to 5 lines, based on OSD function, configurable speed
Auto Cruise	Up to 8 groups, based on OSD function, configurable speed
Continuous Scan	8 line, configurable speed and angles
Angles Display	Support
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600/19,200 bps adjustable
Standard Setting	<ul style="list-style-type: none"> • Available with BNC Cable (LTPM05-A) • Available with network cable (100Mbps) (LTPM05-N)
OSD menu	Available
Preset	Up to 80
Lens Drivien	10 V/6 V software control and adaptive
Lens Interface	Support (pan and tilt preset configuration interface)
Surge Protection	GB/T17626.5-2008
Dimensions (W × H × L)	249 mm × 230 mm × 302 mm (9.80 in × 9.06 in × 11.89 in)
Weight	15 kg (33.1 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- Maximum load 15 kg (33.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Input power: 24 V AC
- Support analogue or network cameras (optional)

Available Models

Model	Support
LTPM05-A	Analogue
LTPM05-N	Network

Tech Specs

Model	LTPM05
Maximum Load	15 kg (33.1 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	24 V AC ± 25 %
Power Consumption	max. 85 W (heater off), max. 95 W (heater on)
Pan Speed	0.01° to 60° per second
Tilt Speed	0.01° to 30° per second
Pan Range	0° to 360° continuous