

LTSU05

Unidad de Pan Tilt para exteriores



Model	LTSU05
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	Available with BNC cable and network cable
Surge Protection	Built-in lightning and surge protection
Internal Usable Size (W x H x L)	105 mm x 85 mm x 340 mm (4.1 in x 3.3 in x 13.4 in)
Dimensions (W x H x L)	223 mm x 521 mm x 496 mm (8.8 in x 20.5 in x 19.5 in)
Weight	25 kg (55.1 lb)
Wavelength	-
Illumination	-
Distance	-
Beam angle	-

*Design and specifications are subject to change without prior notice.

Features

- IP67, NEMA-6 enclosure rating (camera enclosure)
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Wiper included
- Support analogue or network cameras (optional)

Tech Specs

Model	LTSU05
Type	Indoor/Outdoor
Protection Rating	<ul style="list-style-type: none"> • IP67, NEMA-6 enclosure rating (camera enclosure) • IP66, NEMA-4X enclosure rating (pan tilt unit)
Material	High-strength aluminum
Finish	Beige
Input Power	24 V DC/24 V AC
Power	60 W (heater: 25 W), standby max. 15 W
Consumption	
Pan Speed	0.1° to 100° per second
Pan Range	0° to 360° continuous
(Movement in Horizontal Plane)	
Tilt Speed	0.1° to 100° per second
Tilt Range	-90° to 40°
(Movement in Vertical Plane)	
Accuracy	0.1°
Operating Ambient Temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485