

LTSU06

Unidad de Pan Tilt para exteriores



Model	LTSU06
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	Available with BNC cable and network cable
Surge Protection	Built-in lightning and surge protection
Internal Usable Size (W × H × L)	74 mm × 90 mm × 160 mm (2.9 in × 3.5 in × 6.3 in) (single side)
Dimensions (W × H × L)	250 mm × 472 mm × 360 mm (9.8 in × 18.6 in × 14.2 in)
Weight	20 kg (44.1 lb)
Wavelength	-
Illumination	-
Distance	-
Beam angle	-

*Design and specifications are subject to change without prior notice.

Features

- IP67, NEMA-6P enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Wiper included
- Support analogue or network cameras (optional)

Tech Specs

Model	LTSU06
Type	Indoor/Outdoor
Protection Rating	IP67, NEMA-6P enclosure rating
Material	High-strength aluminum
Finish	Beige
Input Power	24 V AC/24 V DC
Power	60 W (heater: 25 W), standby max. 15 W
Consumption	
Pan Speed	0.1° to 100° per second
Pan Range	0° to 360° continuous
(Movement in Horizontal Plane)	
Tilt Speed	0.1° to 100° per second
Tilt Range	-90° to 40°
(Movement in Vertical Plane)	
Accuracy	0.1°
Operating Ambient Temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P