

\*Design and specifications are subject to change without prior notice.

## LTAK05

### Panneau de contrôle avec écran 8 pouces



### Features

- Support Pelco-P/Pelco-D
- Support HD-SDI input
- Support ABS, VGA input
- Joystick for accurate control
- 8-inch TFT LCD Display
- Alarm function and shortcut key available

### Tech Specs

<b>Model</b>	LTAK05
<b>Display</b>	8-inch TFT LCD
<b>Video Input</b>	Composite video (NTSC/PAL), VGA, HD-SDI
<b>Operating Ambient Temperature</b>	-10 °C to 50 °C (14 °F to 122 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Interface Connector</b>	6 pins interface, DB 9 pins female outlet, RJ45
<b>Communication Baud Rate</b>	2,400 bps, 4,800 bps, 9,600 bps, 19,200 bps
<b>Communication Protocols</b>	RS-485, RS-422, RS-232, USB2.0
<b>Transmission Distance</b>	Pelco-D, Pelco-P, Visca, Dahua, Kaikan
<b>Battery</b>	1200 m (3937 ft)
<b>Input Power</b>	Ni-MH 700 mAh
<b>Power Consumption</b>	9 V DC to 12 V DC
<b>Dimensions (L × W × H)</b>	4.2 W
<b>Weight</b>	290 mm × 181 mm × 95 mm (11.4 in × 7.1 in × 3.7 in)
	1.6 kg (3.5 lb)