

# LTAK12

## Panneau de commande

|               |                 |
|---------------|-----------------|
| <b>Model</b>  | <b>LTAK12</b>   |
| <b>Weight</b> | 0.5 kg (1.1 lb) |

\*Design and specifications are subject to change without prior notice.



### Features

- RS-485/USB 2.0 (optional)
- Joystick for accurate control
- LCD Display

### Available Models

| Model      | Communication |
|------------|---------------|
| LTAK12     | RS-485        |
| LTAK12-USB | USB           |

### Tech Specs

| Model                                | LTAK12   |
|--------------------------------------|--|
| <b>Joystick</b>                      | 4D   |
| <b>Control Address</b>               | 0 to 255   |
| <b>Operating Ambient Temperature</b> | 0 °C to 50 °C (32 °F to 131 °F)  |
| <b>Relative Humidity</b>             | 5 % to 95 % noncondensing  |
| <b>Communication</b>                 | <ul style="list-style-type: none"> <li>• RS-485 (<b>LTAK12</b>)</li> <li>• USB 2.0 (<b>LTAK12-USB</b>)</li> </ul>              |
| <b>Communication Baud Rate</b>       | 1,200 bps, 2,400 bps, 4,800 bps, 9,600 bps ( <b>LTAK12</b> )   |
| <b>Protocols</b>                     | Pelco-D, Pelco-P, Dahua, Hik ( <b>LTAK12</b> )   |
| <b>Input Power</b>                   | <ul style="list-style-type: none"> <li>• 12 V DC (<b>LTAK12</b>)</li> <li>• 5 V DC (<b>LTAK12-USB</b>)</li> </ul>              |
| <b>Power Consumption</b>             | <ul style="list-style-type: none"> <li>• 0.6 W maximum (<b>LTAK12</b>)</li> <li>• 0.5 W maximum (<b>LTAK12-USB</b>)</li> </ul> |
| <b>Dimensions (W × H × L)</b>        | 158 mm × 107 mm × 150 mm (6.2 in × 4.2 in × 5.9 in)  |