

LTCN04

Module de caméra zoom 20x



| | |
|--------------------------------------|---|
| Model | LTCN04 |
| Auto gain | Auto/Manual (-3 dB to 28 dB) 16 steps |
| Exposure | -9 dB to 9 dB total 13 grade/OFF |
| Certifications | ONVIF, PSIA, CGI, ISAPI, GB28181 |
| Operating Ambient Temperature | -30 °C to 60 °C (-22 °F to 140 °F) |
| Relative Humidity | 5 % to 95 % noncondensing |
| Input Power | 12 V DC |
| Power Consumption | <ul style="list-style-type: none"> ■ 4 W (zoom/focus does not start) ■ 5 W (zoom/focus start) |
| Dimensions (W × H × L) | 52 mm × 58.6 mm × 96.3 mm (2.1 in × 2.3 in × 3.8 in) |
| Weight | 260 g (0.57 lb) |

*Design and specifications are subject to change without prior notice.

Features

- 1/2.8-inch Sony Progressive Scan CMOS sensor
- 0.008 lux minimum illumination in black and white mode
- H.265/H.264/H.264H/MJPEG compression
- 2-way audio
- Operating temperature range from -10 °C to 60 °C (14 °F to 140 °F)
- ONVIF compliant

Tech Specs

| | |
|--------------------------------------|--|
| Model | LTCN04 |
| Type | Network camera module |
| Image Sensor | 1/2.8-inch Sony Progressive Scan CMOS sensor |
| Lens | f = 5 mm to 117 mm (23X), f/1.5 to f/3.5 |
| Digital Zoom | 16X |
| View of Angle | <ul style="list-style-type: none"> ■ 58.2° (wide) to 2.7° (tele) (horizontal) ■ 34.7° (wide) to 1.5° (tele) (vertical) |
| Mini Focus Distance | 10 mm (wide), 1000 mm (tele) |
| Effective Pixels | 1920 × 1080, 1280 × 720 |
| Minimum Illumination | Color: 1.7 lux W/B: 0.08 lux |
| Electronic Shutter Range | 1/3 to 1/30,000 second |
| Wide Dynamic Range (WDR) | On/off |
| Digital Noise Reduction (DNR) | 0 to 5, total 6 steps |
| Video Compression | H.265/H.264/H.264H/MJPEG |
| Audio Compression | G.711/G.722.1/G.726/MP2L2 |
| Frame Rate | 1080p25/30, 1080i25/30 |
| WhiteBalance | Auto/indoor/outdoor/OPW/ATW/manual |