

LTCN08

Caméra Dôme 8 MP



Features

- IP66, NEMA-4X enclosure rating
- 1/2.5-inch Sony Starvis 8.51 MP image sensor
- 0.05 lux minimum illumination in color mode
- Megapixel f = 3.6 to 11 mm varifocal lens
- H.265/H.264/MJPEG compression
- Power over Ethernet (PoE), IEEE 802.3af
- Operating temperature range from -10 °C to 50 °C (14 °F to 122 °F)
- Automatic removable IR cut filter for IR sensitivity at night
- ONVIF compliant

Tech Specs

| | |
|--------------------------------------|---|
| Model | LTCN08 |
| Type | Dome camera |
| Protection Rating | IP66, NEMA-4X enclosure rating |
| Image Sensor | 1/2.5-inch Sony Starvis 8.51 MP image sensor |
| Lens | Megapixel f = 3.6 to 11 mm varifocal lens |
| Effective Pixels | 3864 × 2202 |
| Minimum Illumination | <ul style="list-style-type: none"> ■ Color mode: 0.05 lux at F 1.2, AGC on ■ Black and white mode: 0 lux (LED on) |
| Electronic Shutter Range | 1/30 s to 1/30,000 s |
| IR Cut Filter | Automatically switches |
| Wide Dynamic Range (WDR) | Digital WDR |
| Digital Noise Reduction (DNR) | 2D/3DNR |
| Video Compression | H.265/H264/MJPEG |
| Motion Detection | 432 zone (of/off, 1 to 5 step) |
| Privacy Masking | Off/On (16 programmable zones) |
| Day and Night | Color/B/W/Auto |
| Frame Rate | Max. 30 fps for all resolution |
| Streaming Capability | Triple stream (stream 1, 2, 3) RTP/RTSP, Unicast RTP, Multicast RTP |
| Certifications | ONVIF, PSIA, CGI, ISAPI, GB28181 |
| Supported Protocols | TCP/IP, UDP/IP, RTP, RTSP, RTCP, NTP, HTTP, DHCP, FTP, SMTP, DNS, DDNS |
| ONVIF | Ver 17.06 |
| LEDs | 24 pieces |
| Illumination Distance | 20 m (65.6 ft) |
| Operating Ambient Temperature | -10 °C to 50 °C (14 °F to 122 °F) |
| Relative Humidity | 5 % to 95 % noncondensing |
| Input Power | 12 V DC ± 10 %/PoE current Max. 750 mA |
| Power Consumption | Max. 12 W |
| Dimensions (Ø × H) | 136 mm × 115 mm (5.4 in × 4.5 in) |
| Weight | 600 g (1.3 lb) |

*Design and specifications are subject to change without prior notice.