

LTEV15

Caisson de caméra à balayage linéaire IP66



Model	LTEV15
Area (W × H)	
Window Thickness	3 mm (0.12 in), tempered glass
Internal Usable	160 mm × 136 mm × 357 mm (6.3 in × 5.7 in × 14.1 in)
Size (W × H × L)	(LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
Heater Control	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
Blower Control	On at 40 °C ± 3 °C (104 °F ± 5 °F), off at 30 °C ± 3 °C (86 °F ± 5 °F) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
Operating Ambient Temperature	-40 °C to 60 °C (-40 °F to 140 °F) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
Weight	<ul style="list-style-type: none"> • 4 kg (8.8 lb) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4) • Max. 4.7 kg (10.4 lb) (wall mount bracket included) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
Certifications	CE, FCC, RoHS
Related Products	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- Designed for indoor and outdoor applications
- Included sunshield
- Input power: 12 V DC/24 V AC/220 V AC (available)
- Adjustable sliding camera tray

Available Models

Model	Heater	Blower	Input Power
LTEV15-3-1	+	+	12 V DC
LTEV15-3-2	+	+	24 V AC
LTEV15-3-4	+	+	220 V AC

Tech Specs

Model	LTEV15
Type	Indoor/Outdoor, side opening, for lin scan camera
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum
Finish	White polyester powder coat
Input Power	<ul style="list-style-type: none"> • 12 V DC (LTEV15-3-1) • 24 V AC (LTEV15-3-2) • 220 V AC (LTEV15-3-4)
Output Power	-
Power Consumption	<ul style="list-style-type: none"> • Heater (12 V DC): 4.2 W (350 mA) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4) • Blower: 1.68 W (140 mA)
Dimensions (W × H × L)	162 mm × 166 mm × 486.5 mm (6.4 in × 6.5 in × 19.2 in) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
Window Viewing	-