

# LTEX07

## Caisson de dôme antidéflagrant (SS304)

Ø 130 mm (5,1 in), caisson de dôme antidéflagrant, SS304



<b>Model</b>	<b>LTEX07</b>
<b>Area (Ø)</b>	
<b>Weight</b>	4.0 kg (8.8 lb)
<b>Material</b>	<ul style="list-style-type: none"> <li>■ AISI 304 stainless steel (<b>LTEX07</b>)</li> <li>■ AISI 316L stainless steel (<b>LTEX07-L</b>)</li> </ul>

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- Dome housing
- Operating temperature range from -30 °C to 70 °C (-22 °F to 158 °F)
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)

### Available Models

Model	Material
LTEX07	AISI 304 stainless steel
LTEX07-L	AISI 316L stainless steel

### Tech Specs

Model	LTEX07
<b>Type</b>	Dome housing
<b>Atmospheric Pressure</b>	80 kPa to 106 kPa
<b>Operating Ambient Temperature</b>	-30 °C to 70 °C (-22 °F to 158 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Protection Rating</b>	<ul style="list-style-type: none"> <li>■ Ex d IIC T6 Gb explosion-proof marking</li> <li>■ IP66, NEMA-4X enclosure rating</li> </ul>
<b>Outlet Hole Thread</b>	G-1/2"
<b>Size</b>	
<b>Dimensions (Ø × L)</b>	130 mm × 129 mm (5.1 in × 5.1 in)
<b>Internal Usable Size (Ø × L)</b>	97 mm × 100 mm (3.8 in × 3.9 in)
<b>Window Viewing</b>	-