

# LTEX15

Caisson de caméra de climatisation antidéflagrant IP68 (SS304)

<b>Model</b>	<b>LTEX15</b>
<b>Window Viewing Area (Ø)</b>	
<b>Weight</b>	7 kg (21.38 lb)
<b>Material</b>	<ul style="list-style-type: none"> <li>• AISI 304 stainless steel (<b>LTEX15</b>)</li> <li>• AISI 316L stainless steel (<b>LTEX15-L</b>)</li> </ul>
<b>Heater Control</b>	-
<b>Related Products</b>	-

\*Design and specifications are subject to change without prior notice.



## Features

- IP68, NEMA-6P enclosure rating
- Built-in automatic air-conditioning
- Operating temperature range from -40 °C to 65 °C (-49 °F to 149 °F)
- Ex d IIB T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)

## Available Models

Model	Material
<b>LTEX15</b>	AISI 304 stainless steel
<b>LTEX15-L</b>	AISI 316L stainless steel

## Tech Specs

Model	LTEX15
<b>Type</b>	Back opening
<b>Atmospheric Pressure</b>	86 kPa to 106 kPa
<b>Operating Ambient Temperature</b>	-40 °C to 65 °C (-49 °F to 149 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Protection Rating</b>	<ul style="list-style-type: none"> <li>• Ex d IIB T6 Gb explosion-proof marking</li> <li>• IP68, NEMA-6P enclosure rating</li> </ul>
<b>Input Power</b>	12 V DC/24 V AC
<b>Dimensions (Ø × L)</b>	155 mm × 330 mm (6.10 in × 12.99 in)
<b>Internal Usable Size (Ø × L)</b>	101 mm × 240 mm (3.98 in × 9.45 in)
<b>Window Thickness</b>	-