

# LTILO4

## Illuminateur laser infrarouge

Distance d'éclairage jusqu'à 2 000 m (6 562 pieds)



### Features

- Illuminator with distance up to 2,000 m (6,562 ft)
- Motor driven beam angle from 0.3° to 42° adjustable
- Synchronized with camera zoom
- Input power: 24 V DC
- Semi-covert (808 nm) wavelength

### Tech Specs

<b>Model</b>	LTILO4
<b>Input Power</b>	24 V DC
<b>Power</b>	40 W
<b>Consumption</b>	
<b>Dimensions (W × H × L)</b>	56 mm × 60 mm × 132 mm (2.2 in × 2.4 in × 5.2 in)
<b>Operating Ambient Temperature</b>	-20 °C to 50 °C (-4 °F to 122 °F)
<b>Storage Temperature</b>	-40 °C to 80 °C (-40 °F to 176 °F)
<b>Weight</b>	2 kg (4.4 lb)
<b>Wavelength</b>	808 ± 5 nm
<b>Beam Angle</b>	0.3° to 42°, motor driven
<b>Illumination Distance</b>	up to 2,000 m (6,562 ft)
<b>Laser Lifetime</b>	30,000 hours
<b>Communication</b>	RS485

\*Design and specifications are subject to change without prior notice.