

LTPD01

Caisson de dôme PTZ extérieur

12,7 cm (5 pouces), boîtier de dôme rapide PTZ



Model	LTPD01
Speed	
Standard Setting	Available with BNC cable
OSD menu	Available
Preset	Up to 226 preset positions, 8 scanning modes
Surge Protection	-
Dimensions (W × H × L)	262 mm × 382.7 mm × 150 mm (10.3 in × 15.1 in × 5.9 in)
Weight	3 kg (6.61 lb)
Wavelength	850 nm
Illumination Distance	100 m (328.1 ft)
Beam Angle	-
LEDs	9 pieces
LED Lifetime	> 25,000 hours
Light On/Off	On when illumination is lower than 4 lux
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Die-cast aluminum construction

Tech Specs

Model	LTPD01
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Die-cast aluminum
Finish	White
Input Power	12 V DC
Power	50 W
Consumption	
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Pan Speed	0° to 300° per second
Tilt Range (Movement in Vertical Plane)	-45° to 45°
Tilt Speed	0 to 270° per second
Accuracy	0.225° ± 0.003°
Atmospheric Pressure	-
Operating Ambient Temperature	-10 °C to 50 °C (-14 °F to 122 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Communication	2,400 bps, 4,800 bps, 9,600 bps adjustable