

LTPM03

Tourelle extérieur

IP66, charge maximale de 9 kg (19,8 lb), vitesse panoramique et inclinaison réglables, construction en alliage d'aluminium



Model	LTPM03
(Movement in Horizontal Plane)	
Tilt Range	-60° to 10°
(Movement in Vertical Plane)	
Accuracy	0.4°
Operating Ambient Temperature	-10 °C to 50 °C (-14 °F to 122 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600/19,200 bps adjustable
Standard Setting	<ul style="list-style-type: none"> Available with BNC Cable (LTPM03-A-6) Available with network cable (100Mbps) (LTPM03-N-6)
OSD menu	Available
Preset	Up to 226
Surge Protection	GB/T17626.5-2008
Dimensions (W × H × L)	165 mm × 263 mm × 146 mm (6.5 in × 10.4 in × 5.8 in)
Weight	7 kg (15.4 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- Maximum load 9 kg (19.8 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Input power: 24 V DC
- Support analogue or network cameras (optional)

Available Models

Model	Support
LTPM03-A-6	Analogue
LTPM03-N-6	Network

Tech Specs

Model	LTPM03
Maximum Load	9 kg (19.8 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	24 V DC
Power	30 W
Consumption	
Pan Speed	0.4° to 10° per second
Tilt Speed	0.4° to 2.5° per second
Pan Range	0° to 360° continuous