

LTPM11

Unité de panoramique et d'inclinaison extérieure pour des charges jusqu'à 9 kg (19,8 lb)

IP66, charge maximale de 9 kg (19,8 lb), vitesse panoramique et inclinaison réglables, construction en alliage d'aluminium



Model	LTPM11
Accuracy	0.1°
Operating Ambient Temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	Available with BNC cable and network cable
Dimensions (W × H × L)	223 mm × 350 mm × 250 mm (8.8 in × 13.8 in × 9.8 in)
Packing Dimensions (W × H × L)	340 mm × 310 mm × 820 mm (13.4 in × 12.2 in × 32.3 in)
Weight	10 kg (22.0 lb)

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)

Tech Specs

Model	LTPM11
Maximum Load	9 kg (19.8 lb)
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	High-strength aluminum
Finish	Beige
Input Power	24 V DC/24 V AC
Power Consumption	60 W (heater: 25 W), standby max. 15 W
Pan Speed	0.1° to 100° per second
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Tilt Speed	0.1° to 100° per second
Tilt Range (Movement in Vertical Plane)	-90° to 40°