

# LTSU06

Unité de panoramique et d'inclinaison extérieure



|   |   |
|---|---|
| <b>Model</b>                            | <b>LTSU06</b>   |
| <b>Communication</b>                    | RS-485  |
| <b>Protocols</b>                        | Pelco-D, Pelco-P  |
| <b>Baud Rate</b>                        | 2,400/4,800/9,600 bps adjustable                                |
| <b>Standard Setting</b>                 | Available with BNC cable and network cable                      |
| <b>Surge Protection</b>                 | Built-in lightning and surge protection                         |
| <b>Internal Usable Size (W × H × L)</b> | 74 mm × 90 mm × 160 mm (2.9 in × 3.5 in × 6.3 in) (single side) |
| <b>Dimensions (W × H × L)</b>           | 250 mm × 472 mm × 360 mm (9.8 in × 18.6 in × 14.2 in)           |
| <b>Weight</b>                           | 20 kg (44.1 lb)   |
| <b>Wavelength</b>                       | -   |
| <b>Illumination Distance</b>            | -   |
| <b>Beam angle</b>                       | -   |

\*Design and specifications are subject to change without prior notice.

## Features

- IP67, NEMA-6P enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Wiper included
- Support analogue or network cameras (optional)

## Tech Specs

|   |  |
|---|--|
| <b>Model</b>                                    | LTSU06                                 |
| <b>Type</b>                                     | Indoor/Outdoor                         |
| <b>Protection Rating</b>                        | IP67, NEMA-6P enclosure rating         |
| <b>Material</b>                                 | High-strength aluminum                 |
| <b>Finish</b>                                   | Beige                                  |
| <b>Input Power</b>                              | 24 V AC/24 V DC                        |
| <b>Power</b>                                    | 60 W (heater: 25 W), standby max. 15 W |
| <b>Consumption</b>                              |  |
| <b>Pan Speed</b>                                | 0.1° to 100° per second                |
| <b>Pan Range (Movement in Horizontal Plane)</b> | 0° to 360° continuous                  |
| <b>Tilt Speed</b>                               | 0.1° to 100° per second                |
| <b>Tilt Range (Movement in Vertical Plane)</b>  | -90° to 40°                            |
| <b>Accuracy</b>                                 | 0.1°                                   |
| <b>Operating Ambient Temperature</b>            | -30 °C to 60 °C (-22 °F to 140 °F)     |
| <b>Relative Humidity</b>                        | 5 % to 95 % noncondensing              |