

# LTSU08

## Unité de panoramique et d'inclinaison extérieure



<b>Model</b>	<b>LTSU08</b>
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D, Pelco-P
<b>Baud Rate</b>	2,400/4,800/9,600/19,200 bps adjustable
<b>Standard Setting</b>	Available with BNC cable and network cable
<b>Surge Protection</b>	Built-in lightning and surge protection
<b>Internal Usable Size (W × H × L)</b>	250 mm × 200 mm × 800 mm (9.8 in × 7.9 in × 31.5 in)
<b>Dimensions (W × H × L)</b>	342 mm × 641 mm × 930 mm (13.5 in × 25.2 in × 36.6 in)
<b>Weight</b>	38 kg (83.8 lb)
<b>Wavelength</b>	-
<b>Illumination Distance</b>	-
<b>Beam angle</b>	-

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Wiper (optional)
- Support analogue or network cameras (optional)

### Tech Specs

<b>Model</b>	<b>LTSU08</b>
<b>Type</b>	Indoor/Outdoor
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	High-strength aluminum
<b>Finish</b>	Beige
<b>Input Power</b>	24 V AC/24 V DC
<b>Power</b>	85 W (heater: 10 W), standby max. 15 W
<b>Consumption</b>	
<b>Pan Speed</b>	0.011° to 30° per second
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360° continuous
<b>Tilt Speed</b>	0.01° to 15° per second
<b>Tilt Range (Movement in Vertical Plane)</b>	<ul style="list-style-type: none"> <li>• -45° to 45° for load 50 kg (110.2 lb) (factory setting)</li> <li>• -60° to 60° for load 40 kg (88.2 lb)</li> <li>• -80° to 80° for load 26 kg (57.3 lb)</li> <li>• -90° to 90° for double load</li> </ul>
<b>Accuracy</b>	0.0225° ± 0.003°
<b>Operating Ambient Temperature</b>	-35 °C to 65 °C (-31 °F to 149 °F)