

# LTSV01

## Caméra PTZ IR anti-vibration

IP66, conception anti-vibration adaptée à une utilisation en véhicule, éclairage IR avec une distance jusqu'à 30 m (98,4 pieds), essuie-glace inclus



|                                      |   |
|--------------------------------------|---|
| <b>Model</b>                         | <b>LTSV01</b>   |
| <b>Relative Humidity</b>             | 5 % to 95 % noncondensing                               |
| <b>Operating Ambient Temperature</b> | -35 °C to 65 °C (-31 °F to 149 °F)                      |
| <b>Communication</b>                 | RS-485  |
| <b>Protocols</b>                     | Pelco-D/Pelco-P   |
| <b>Baud Rate</b>                     | 2,400/4,800/9,600/19,200 bps adjustable                 |
| <b>Dimensions (W × H × L)</b>        | 235 mm × 176 mm × 375 mm (9.25 in × 6.93 in × 14.76 in) |
| <b>Weight</b>                        | 7.2 kg (15.87 lb)                                       |
| <b>Wavelength</b>                    | 850 nm  |
| <b>Illumination Distance</b>         | 30 m (98.4 ft)  |
| <b>Beam angle</b>                    | 6 to 60°  |

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-6P enclosure rating
- Anti-vibration design suitable for vehicle use
- Built-in IR illuminator with distance up to 30 m (98.4 ft)
- Pan and tilt speed adjustable
- Wiper included

### Tech Specs

|   |  |
|---|--|
| <b>Model</b>                                    | <b>LTSV01</b>  |
| <b>Type</b>                                     | Indoor/Outdoor, anti-vibration   |
| <b>Protection Rating</b>                        | IP66, NEMA-4X enclosure rating   |
| <b>Material</b>                                 | High-strength aluminum   |
| <b>Finish</b>                                   | Silver   |
| <b>Input Power</b>                              | 10.5 V DC to 18 V DC (3.5 A)   |
| <b>Power</b>                                    | 23 W   |
| <b>Consumption</b>                              |  |
| <b>Pan Range (Movement in Horizontal Plane)</b> | 0° to 360° continuous  |
| <b>Pan Speed</b>                                | <ul style="list-style-type: none"> <li>▪ 0° to 80° per second adjustable</li> <li>▪ Preset speed: 0° to 80° per second adjustable</li> </ul> |
| <b>Tilt Range (Movement in Vertical Plane)</b>  | -90° to 90°  |
| <b>Tilt Speed</b>                               | <ul style="list-style-type: none"> <li>▪ 0° to 40° per second adjustable</li> <li>▪ Preset speed: 100° per second</li> </ul>                 |
| <b>Accuracy</b>                                 | 0.225° ± 0.003°  |
| <b>Atmospheric Pressure</b>                     | 80 kPa to 106 kPa  |