

# LTSV02

## Caméra PTZ anti-vibration à lumière blanche

IP66, conception anti-vibration adaptée à une utilisation dans un véhicule, éclairage à lumière blanche avec une distance jusqu'à 400 m (1312,3 pieds), essuie-glace inclus



<b>Model</b>	<b>LTSV02</b>
<b>Pressure</b>	
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Operating Ambient Temperature</b>	-35 °C to 65 °C (-31 °F to 149 °F)
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D/Pelco-P
<b>Baud Rate</b>	2,400/4,800/9,600/19,200 bps adjustable
<b>Dimensions (W × H × L)</b>	235 mm × 176 mm × 375 mm (9.25 in × 6.93 in × 14.76 in)
<b>Weight</b>	7.2 kg (15.87 lb)
<b>Colour</b>	6000 K
<b>Temperature</b>	
<b>Wavelength</b>	-
<b>Illumination Distance</b>	400 m (1312.3 ft)
<b>Beam angle</b>	6° to 60°

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-6P enclosure rating
- Anti-vibration design suitable for vehicle use
- Built-in white light illuminator with distance up to 400 m (1312.3 ft)
- Pan and tilt speed adjustable
- Wiper included

### Tech Specs

<b>Model</b>	<b>LTSV02</b>
<b>Type</b>	Indoor/Outdoor, anti-vibration
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	High-strength aluminum
<b>Finish</b>	Silver
<b>Input Power</b>	10.5 V DC to 18 V DC (3.5 A)
<b>Power</b>	28 W
<b>Consumption</b>	
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360° continuous
<b>Pan Speed</b>	<ul style="list-style-type: none"> <li>■ 0° to 80° per second adjustable</li> <li>■ Preset speed: 0° to 80° per second adjustable</li> </ul>
<b>Tilt Range (Movement in Vertical Plane)</b>	-90° to 90°
<b>Tilt Speed</b>	<ul style="list-style-type: none"> <li>■ 0° to 40° per second adjustable</li> <li>■ Preset speed: 100° per second</li> </ul>
<b>Accuracy</b>	0.225° ± 0.003°
<b>Atmospheric</b>	80 kPa to 106 kPa