

# LTAB03

## 防爆パワーボックス



### Features

- IP66, NEMA-6P enclosure rating
- Exd II CT6 explosion-proof marking

### Tech Specs

|   |  |  |
|---|--|--|
| <b>Model</b>                            | LTAB03   |  |
| <b>Type</b>                             | Indoor/Outdoor, top opening  |  |
| <b>Protection Rating</b>                | <ul style="list-style-type: none"> <li>▪ IP66, NEMA-4X enclosure rating</li> <li>▪ Exd II CT6</li> </ul> |  |
| <b>Material</b>                         | SS304/SS316L   |  |
| <b>Finish</b>                           | Stainless steel original color   |  |
| <b>Atmospheric Pressure</b>             | 80 kPa to 106 kPa  |  |
| <b>Operating Ambient Temperature</b>    | -25 °C to 60 °C (-13 °F to 140 °F)   |  |
| <b>Relative Humidity</b>                | 5 % to 95 % noncondensing  |  |
| <b>Cable Fitting Thread</b>             | G-3/4"   |  |
| <b>Cable Fitting Numbers</b>            | 3  |  |
| <b>Internal Usable Size (L × W × H)</b> | 160 mm × 210 mm × 100 mm (6.30 in × 8.27 in × 3.94 in)   |  |
| <b>Dimensions (L × W × H)</b>           | 183 mm × 233 mm × 123 mm (7.20 in × 9.17 in × 4.84 in)   |  |
| <b>Weight</b>                           | -  |  |

\*Design and specifications are subject to change without prior notice.