

LTCN15

30倍カメラモジュール



Model	LTCN05
WhiteBalance	Auto tracing white/Auto white/Manual
Analog Gain/Digital Max Gain	1 to 30
Exposure	Auto/Flat/Spot/Center
PTZ Control Protocol	40 types of control protocol including Pelco-D, Pelco-P, Visca
Certifications	ONVIF, PSIA
Operating Ambient Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Relative Humidity	5 % to 95 % noncondensing
Input Power	12 V DC
Power Consumption	Max. 5.4 W
Dimensions (L × W × H)	51.6 mm × 61 mm × 101 mm (2.0 in × 2.4 in × 4.0 in)
Weight	294 g (0.65 lb)

*Design and specifications are subject to change without prior notice.

Features

- 1/2.8-inch Sony CMOS sensor
- 30X optical zoom, 16X digital zoom
- Max 60 fps (1920 × 1080)
- H.265/H.264/MJPEG compression
- True WDR
- Autofocus
- ONVIF, PSIA compliant

Tech Specs

Model	LTCN05
Type	Network camera module
Image Sensor	1/2.8-inch Sony CMOS
Lens	f = 5.2 mm to 156 mm (30X), f/1.3 to f/4.8
Digital Zoom	16X
View of Angle	<ul style="list-style-type: none"> ▪ Horizontal: 58.1° (wide) to 2.9° (tele) ▪ Vertical: 34.7° (wide) to 1.6° (tele) ▪ Diagonal: 67.1° (wide) to 2.78° (tele)
Mini Focus Distance	1 m to 10 m
Effective Pixels	352 × 240 to 1920 × 1080
Minimum Illumination	<ul style="list-style-type: none"> ▪ Color: 0.06 lux at 1/15 sec, 50 IRE ▪ Day and Night: 0.0003 lux at 1/15 sec, 50 IRE
Electronic Shutter Range	1/1 to 1/100000 second
Wide Dynamic Range (WDR)	Level 1 to level 7
Digital Noise Reduction (DNR)	0 to 5, total 6 steps
Video Compression	H.265/H.264/MJPEG
Audio Compression	G.711/AAC
Frame Rate	Max. 60 fps