

# LTCN05

## 30倍カメラモジュール



<b>Model</b>	LTCN05
<b>WhiteBalance</b>	Auto tracing white/Auto white/Manual
<b>Analog Gain/Digital Max Gain</b>	1 to 30
<b>Exposure</b>	Auto/Flat/Spot/Center
<b>PTZ Control Protocol</b>	40 types of control protocol including Pelco-D, Pelco-P, Visca
<b>Certifications</b>	ONVIF, PSIA
<b>Operating Ambient Temperature</b>	-10 °C to 50 °C (14 °F to 122 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Input Power</b>	12 V DC
<b>Power Consumption</b>	Max. 5.4 W
<b>Dimensions (L × W × H)</b>	51.6 mm × 61 mm × 101 mm (2.0 in × 2.4 in × 4.0 in)
<b>Weight</b>	294 g (0.65 lb)

\*Design and specifications are subject to change without prior notice.

### Features

- 1/2.8-inch Sony CMOS sensor
- 30X optical zoom, 16X digital zoom
- Max 60 fps (1920 × 1080)
- H.265/H.264/MJPEG compression
- True WDR
- Autofocus
- ONVIF, PSIA compliant

### Tech Specs

<b>Model</b>	LTCN05
<b>Type</b>	Network camera module
<b>Image Sensor</b>	1/2.8-inch Sony CMOS
<b>Lens</b>	f = 5.2 mm to 156 mm (30X), f/1.3 to f/4.8
<b>Digital Zoom</b>	16X
<b>View of Angle</b>	<ul style="list-style-type: none"> <li>▪ Horizontal: 58.1° (wide) to 2.9° (tele)</li> <li>▪ Vertical: 34.7° (wide) to 1.6° (tele)</li> <li>▪ Diagonal: 67.1° (wide) to 2.78° (tele)</li> </ul>
<b>Mini Focus Distance</b>	1 m to 10 m
<b>Effective Pixels</b>	352 × 240 to 1920 × 1080
<b>Minimum Illumination</b>	<ul style="list-style-type: none"> <li>▪ Color: 0.06 lux at 1/15 sec, 50 IRE</li> <li>▪ Day and Night: 0.0003 lux at 1/15 sec, 50 IRE</li> </ul>
<b>Electronic Shutter Range</b>	1/1 to 1/100000 second
<b>Wide Dynamic Range (WDR)</b>	Level 1 to level 7
<b>Digital Noise Reduction (DNR)</b>	0 to 5, total 6 steps
<b>Video Compression</b>	H.265/H.264/MJPEG
<b>Audio Compression</b>	G.711/AAC
<b>Frame Rate</b>	Max. 60 fps