

# LTES10

## IP68 Stainless Steel Dome Housing

Ø 215 mm (8.4 in), SS304



<b>Model</b>	LTES10
<b>Material</b>	<ul style="list-style-type: none"> <li>• AISI 304 stainless steel (LTES10)</li> <li>• AISI 316L stainless steel (LTES10-L)</li> </ul>
<b>Note</b>	Strongly recommend to send camera module for LonTrend Factory's assemblage or choose compact solution directly.

\*Design and specifications are subject to change without prior notice.

### Features

- IP68, NEMA-6P enclosure rating
- Dome housing
- Operating temperature range from -45 °C to 60 °C (-49 °F to 140 °F)
- AISI 304/316L stainless steel construction (available)

### Available Models

Model	Material	Window Viewing Area (Ø)
LTES10	AISI 304 stainless steel	98 mm (3.9 in)
LTES10-L	AISI 316L stainless steel	98 mm (3.9 in)

### Tech Specs

Model	LTES10
<b>Type</b>	Dome housing
<b>Atmospheric Pressure</b>	86 kPa to 106 kPa
<b>Operating Ambient Temperature</b>	-45 °C to 60 °C (-49 °F to 140 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Protection Rating</b>	IP68, NEMA-6P enclosure rating
<b>Outlet Hole Thread</b>	G-3/4"
<b>Size</b>	
<b>Dimensions (Ø × L)</b>	215 mm × 128 mm (8.5 in × 5.0 in)
<b>Internal Usable Size (Ø × L)</b>	145 mm × 108 mm (5.7 in × 4.3 in)
<b>Window Viewing Area (Ø)</b>	98 mm (3.9 in)
<b>Weight</b>	6.5 kg (14.3 lb)