

LTES20

IP68 Wide Window IK10 Camera Housing

| | |
|------------------|-----------------|
| Model | LTES20 |
| Weight | 1.5 kg (3.3 lb) |
| Certifications | CE, FCC, RoHS |
| Wavelength | - |
| Illumination | - |
| Distance | - |
| Beam Angle | - |
| LEDs | - |
| LED Lifetime | - |
| Light On/Off | - |
| Related Products | - |

*Design and specifications are subject to change without prior notice.



Features

- IP68, NEMA-6P enclosure rating
- IK10 impact resistance
- 4.5 mm thickness tempered polycarbonate with anti-fog coated
- Designed for indoor and outdoor applications
- Included sunshield

Tech Specs

| | |
|----------------------------------|--|
| Model | LTES20 |
| Type | Indoor/Outdoor, top opening, for low operating ambient temperature |
| Protection Rating | <ul style="list-style-type: none"> • IP68, NEMA-6P enclosure rating • IK10 |
| Material | Stainless and aluminum construction approve by NEMA TS2 |
| Finish | Black polyester powder coat |
| Input Power | - |
| Output Power | - |
| Power Consumption | - |
| Dimensions (W × H × L) | 204.6 mm × 90.9 mm × 175 mm (8.1 in × 3.6 in × 6.9 in) |
| Window Viewing Area (W × H) | 140 mm × 50 mm (5.5 in × 2.0 in) |
| Window Thickness | 4.5 mm (0.2 in), tempered polycarbonate with anti-fog coated |
| Internal Usable Size (W × H × L) | 155 mm × 57 mm × 145 mm (6.1 in × 2.2 in × 5.7 in) |
| Heater Control | - |
| Blower Control | - |
| Operating Ambient Temperature | -30 °C to 70 °C (-22 °F to 158 °F) |