

# LTEX04

## IP66 Explosion Proof Camera Housing (SS304)

42 cm (16.5 in), explosion proof camera housing, included wiper and sunshield, SS304

<b>Model</b>	LTEX04
<b>Internal Usable Size (W × H × L)</b>	114 mm × 210 mm (3.15 in × 8.27 in)
<b>Window Thickness</b>	12 mm (0.47 in)
<b>Window Viewing Area (Ø)</b>	69.5 mm (2.74 in)
<b>Weight</b>	<ul style="list-style-type: none"> <li>• 11 kg (24.25 lb)</li> <li>• 12.8 kg (28.22 lb) (wall mount bracket included)</li> </ul>
<b>Material</b>	<ul style="list-style-type: none"> <li>• AISI 304 stainless steel (LTEX04)</li> <li>• AISI 316L stainless steel (LTEX04-L)</li> </ul>
<b>Heater Control</b>	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (optional)
<b>Related Products</b>	LTMH08, LTPX01, LTMH08-L

\*Design and specifications are subject to change without prior notice.



### Features

- IP66, NEMA-4X enclosure rating
- Operating temperature range from -25 °C to 60 °C (-13 °F to 140 °F)
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)
- Included wiper and sunshield

### Available Models

Model	Material
LTEX04	AISI 304 stainless steel
LTEX04-L	AISI 316L stainless steel

### Tech Specs

Model	LTEX04
<b>Type</b>	Back opening
<b>Atmospheric Pressure</b>	80 kPa to 106 kPa
<b>Operating Ambient Temperature</b>	-25 °C to 60 °C (-13 °F to 140 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Protection Rating</b>	<ul style="list-style-type: none"> <li>• Ex d IIC T6 Gb explosion-proof marking</li> <li>• IP66, NEMA-4X enclosure rating</li> </ul>
<b>Input Power</b>	85 V AC to 265 V AC, 24 V AC
<b>Dimensions (W × H × L)</b>	195 mm × 194 mm × 420 mm (7.68 in × 7.64 in × 16.54 in)