

LTEX15

IP68 Explosion Proof Camera Housing with Heat Sink (SS304)

Model	LTEX15
Area (Ø)	
Window Thickness	-
Weight	9.5 kg (20.9 lb) (without wall mount bracket)
Material	<ul style="list-style-type: none"> • AISI 304 stainless steel (LTEX15) • AISI 316L stainless steel (LTEX15-L)
Heater Control	-
Related Products	-

*Design and specifications are subject to change without prior notice.



Features

- IP68, NEMA-6P enclosure rating
- Built-in automatic air-conditioning
- Operating temperature range from -40 °C to 65 °C (-49 °F to 149 °F)
- Ex d IIB T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)

Available Models

Model	Material
LTEX15	AISI 304 stainless steel
LTEX15-L	AISI 316L stainless steel

Tech Specs

Model	LTEX15
Type	Back opening
Atmospheric Pressure	86 kPa to 106 kPa
Operating Ambient Temperature	-40 °C to 65 °C (-49 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	<ul style="list-style-type: none"> • Ex d IIB T6 Gb explosion-proof marking • IP68, NEMA-6P enclosure rating
Input Power	12 V DC/24 V AC
Dimensions (Ø × L)	160 mm × 340 mm (6.3 in × 13.4 in)
Internal Usable Size (Ø × L)	120 mm × 260 mm (4.7 in × 10.2 in)
Window Viewing	67 mm (2.6 in)